



Technical specification

Armlight suitable for various types of display systems. Coupling box with or without switch. Clips made of aluminium or plastic, can be fitted below the coupling box for the relevant type of display system. Glass lens snaps in position and held by springs.

Model and colours

Available in black or grey. Supplied with 300mm arm.

Area of use

Normally two fittings of the above type are used for a portable 4x2 display.

Technical data

Mains (input) voltage	220-230 V
Total weight	0,5 kg
Form of protection	IP 20, class II/I
Colour temperature	3 000 K
Lamp type	120W 78mm tubular halogen
Lamp holder	R7s
Energy consumption	120 W
Start time	Instant
Safety glass	Included
Reflector	High quality anodized reflector
Beam spreads	Flood

Art no	Description	Colour
100-502-20 89226D1030S	Class II with switch	Black
100-502-30 89226G1030S	Class II with switch	Grey
100-501-20 89226D3030S	Class I with switch	Black
100-501-30 89226G3030S	Class I with switch	Grey
100-520-20 89206D1030S	Class II without switch	Black
100-520-30 89206G1030S	Class II without switch	Grey
100-521-20 89206D3030S	Class I without switch	Black
100-521-30 89206G3030S	Class I without switch	Grey

Note

Final shipping destination may require minor modifications of components as well as catalogue numbers, be sure to state the country in which the fixtures will be used.