



Technical specification

Linear down light for LED tubes. Reflector with flood beam spread. Housing of powder painted sheet metal. Built in electronic.

Model and colors

Available in white.

Area of use

LED light for indoor applications, suitable for general lighting.

Technical data

| | |
|-----------------------------|---------------------------------|
| Mains (input) voltage | 220-240 V |
| LED driver output | Constant voltage 28V, Max 60W |
| Total weight | 4,57 kg |
| Form of protection | IP 20, class I |
| Color temperature | 3 500 K |
| Color rendering index (CRI) | 80+ |
| Luminaire output | 6100 lm |
| Light source | LED |
| Operating position | Vertical |
| Lamp holder | NLAB Standard |
| Energy consumption | 59 W |
| Control gear | Electronic |
| Start time | Instant |
| Driver | Separate |
| Reflector | High quality anodized reflector |
| Beam spreads | Flood |

| Art no | Description | Color |
|---------|----------------------|-------|
| 204-5xx | GRID LED 1900mm, 830 | White |
| 204-5xx | GRID LED 1900mm, 835 | White |
| 204-5xx | GRID LED 1900mm, 840 | White |
| xx | GRID LED 1700mm, 830 | White |
| xxx | GRID LED 1700mm, 835 | White |
| xx | GRID LED 1700mm, 840 | White |

Note

Final shipping destination may require minor modifications of components as well as article numbers, be sure to state the country in which the fixtures will be used.

Product is still under construction.

Please ask Nordic Light for latest availability update.

For latest performance data please download datasheet from www.nordiclight.com